





Visoglide Plus

Visoglide Plus offers the same contemporary styling and robust performance associated with the system whilst delivering superior thermal performance.

- U Value 1.6 W/m²K
- Air Class 3, 600Pa
- Water Class 7a, 300Pa
- Wind Class AE, 2400Pa
- Colour matched accessories now available Speak with your supplier for details















Visoglide Plus

This adaptable system is suitable for use as either sliding commercial entrances where large opening apertures are required, or as dynamic residential sliding doors that maximise light and give stunning unimpeded views.

Visoglide Plus profiles have been designed to improve both strength and weather resistance. All main sections feature an extended polyamide thermal break that allows Visoglide Plus to achieve a U Value of 1.6 W/m2K when installed with a suitable sealed unit.

Visoglide Plus doors are available in both single and dual colour in wide choice of standard and non-standard finishes including Smart's unique Sensations range of textured colours.

The system is also suitable for use with auto slide opening mechanisms*.

Technical Performance

U Value 1.6 W/m²K (When using a 1.0 W/m²K centre pane)

Air Class 3, 600Pa

Water Class 7a, 300Pa

Wind Class AE, 2400Pa

Glass up to 38mm

Dual Colour Yes

Security Multipoint locking

Dimensions

Frame Width 53mm
Frame Depth 100mm
Max Sash Weight 80kg


Glass 38mm double or triple glazed sealed units


Design Limitations


Max Sash Weight200kgMax Sash Height2500mm

Max Sash Width Within above limitations

*Auto slide opening mechanisms sold separately

















Smart Systems Limited

Arnolds Way | Yatton | Bristol | North Somerset | BS49 4QN | UK T +44 (0) 1934 876 100 | F +44 (0) 1934 835 169 |

 $\textbf{W} \ \text{www.smartsystems.co.uk} \ | \ \textbf{E} \ \text{sales@smartsystems.co.uk}$

IMS129VGP.201410

The images, drawings and data shown in this brochure are for illustrative purposes only and are not binding in detail, colour or specification. We reserve the right to make changes to the product specification as technical developments dictate and without prior notice. We recommend that the user ensures that they are satisfied the product meets their requirements prior to purchase. ©Smart Systems Ltd 2014